

# POSEIDON<sup>®</sup> AQUA 2

## ULTRASONIC GROUND FOG GENERATOR



### SPECIFICATIONS

<b>AC Power</b>	<b>Input Voltage &amp; Rate</b>	<b>100-120 V, 50/60 Hz</b>
	Current Limiter Type (Heater)	Breaker
	Current Limiter Specifications (Heater)	15 A, 250 V
	Total Power Consumption	1700 W
<b>Heating</b>	Heat Up Time	4.0 min
	Total Power Consumption	500 W
<b>Atomizers</b>	Unit Quantity	2 units
	Power Consumption of each Unit	250 W
	Adjustable	√
	Adjustment Range	OFF/50%/100%
<b>Capacity</b>	Fog Fluid Tank Capacity	0.8 Gal
	Water Chamber Capacity	6 Gal
<b>Output</b>	Adjustable Volume	√
	Volume Adjustment Level/Range	1-100
	Fog Fluid Consumption @ full volume	25.0 mL/min
	Water Consumption @ full volume	240.0 mL/min
	Maximum Continuous Duration @ full volume	Unlimited
	Continuous Output	√
	Max Continuous Output Level	100%
	Fully-loaded Cumulative Output Duration @ full volume	~60 min
<b>Features</b>	Physical Thermostat	√
	Electronic Thermo-Control	√
	Adjustable Output	√
	Adjustable Fan Speed	√
	Auto Water Refill	√
	Low Water Protection	√
	No-Fluid Protection	√
<b>Control</b>	On-device Manual Control	LCD control board
	Wireless Control	W-4 / RF 433MHz / Built-in
	Wired Control	DMX
	Control Protocol	DMX-512
	DMX Channel Range	3
<b>Accessory</b>	Data Connectors	3- and 5-pin XLR
	Ducting Hose	1 pc, Length 3 m, Diameter 100mm (4 inch) Optional
<b>Weight &amp; Dimensions</b>	Net Weight	<b>71 lbs</b>
	Gross Weight	<b>80 lbs</b>
	Machine Dimensions	<b>29 / 15.4 / 17.7 in</b>
	Packing Dimensions	<b>34 / 18.1 / 20 in</b>